



TeloSystems
Bridging Communication Gap

OLED Screen

Intuitive display readable from multiple angles



Radio Design Interface

Powerful compatibility for radio accessories



PTT Button

Textured surface with positive feedback



3G/4G



Android 7.0



IP67
1.5m Drop Test



Crystal Clear Audio



3600
mAh Battery



NFC

TeloPTT TE390

Simplified LTE Handheld Device

Compact, Durable, Handy

www.telosystems.com

TECHNICAL SPECIFICATION

Connectivity		Specifications
Frequency Band	GSM : B2, B3, B5, B8 WCDMA : B1, B2, B5, B8 TD-SCDMA : B34, B39 FDD-LTE : B1, B3, B5, B7, B8, B20 TDD-LTE : B38, B39, B40, B41	
WIFI	IEEE802.11a/b/g/n(1T1R)	
Bluetooth	10M (Min); BT V4.0	
GPS	GPS / AGPS / GLONASS	
Hardware		Specifications
CPU	MTK6737M	
Memory	RAM+ROM: 1GB + 8GB	
Display	OLED 0.97", 128*64 RGB	
Speaker	2.0W, Ø36mm	
Battery	Li-Po 3600mAh	
USB Port	Micro USB2.0	
Sensor	3D Gravity Sensor, Acceleration Sensor	
Software		Specifications
Operation System	Android 7.0	
Physical		Specifications
Protection Rating	IP67, 1.5m drop test	
Working Temperature	-20°C ~ 60°C	
Storage Temperature	-30°C ~ 70°C	



Reliable and Flexible

4/F, Chuangye Building, Seven-Star Park, Yu'an 2nd Road, Bao'an District, Shenzhen, China

www.telosystems.com

Tel: +86 755 86950766

Fax: +86 755 86950708

Email: sales@telosystems.com