

# AIRTALK XSN USB



## Product information

The lightweight, monaural neckband headset for air traffic control applications

- Wideband audio components for HD audio and crystal clear communication
- Optimal microphone positioning thanks to the flexible gooseneck
- Flexible neckband for optimal positioning
- Ear cushions with cooling technology Coolmax® for best wearing comfort
- Diverse connection options and adjustments for nearly all Voice-communication-systems, including USB



## TECHNICAL BASICS

### SPEAKER

Working principle	Dynamic
Impedance	150Ω ± 15% (1kHz)
Sensitivity	121dB ± 3dB (1mW)
Frequency response	100Hz to 5kHz

### ADDITIONAL DATA

Weight	60g
Temperature range	0°C to +40°C
Operation system	Windows 7, or later Linux 2.6, or later
USB Standard	2.0

### MICROPHONE

Working principle	Electret
Direction	Bi- directional
Noise Cancelling	YES
Impedance	1,6kΩ (1kHz)
Frequency response	60Hz to 12kHz
Sensitivity	-51dB ± 3.5dB (1kHz)
Sound pressure level	110dB (S.P.L.)
S/N ratio	58dB (1kHz)

More information about the Product and the corresponding accessories, connection cable and scope of delivery can be found at [www.imtradex.de](http://www.imtradex.de).

TD-ATXSUSB-C-052021-EN